SERFILCO[®]Europe

0

ab

P

3

New 3" Size for even more flow.

Chemical Duty Filter Chambers are available in 1", up to 3" sizes.

Manufactured from plastic materials providing a wide range of chemical resistance. Capable of Flow Rates up to 65m³/h.

These all plastic filter chambers are ideally suited for chemical processing, waste and water treatment, and aqua culture applications.



Filter Cartridges

Filter chambers are designed to accommodate from 1 x 10" up to 26 Columns x 40" Cartridges. Spun Bonded, Depth Wound or Pleated available. Please refer to Euro-004A.

Note: Certain housings accept filter bags and sleeves.

Double Open Ended (DOE) or Single Open Ended (SOE) Standard are DOE, but SOE Single Open Ended for Type 222 "0" Ring are optional on certain models only.

■ Cover Closure Multiple Column Chambers have swing bolt "T" handle covers with a reinforced cover plate, 316 SS Bolts and external Hardware. Fitted with rigid Cartridge guide posts with Knife Edge Hold Down Springs to prevent by pass.

Performance

High flow rates with low pressure drop. Maximum approx 1000l/min (65m³/h). Dependant upon the application and chemical process, temperatures up to 90°C are possible with the correct material selection. External bolted designs are available for maximum pressures to 140psi (9.5 Bar).

- Choice of Materials Plastic Materials PVC/CPVC, Polypropylene and PVDF. Please consult our Chemical Resistance Guide for selection.
- Robust Construction Strong large wall thickness chambers with one piece shell/ base assembly to prevent leakage. 2" and 3" sizes have solid machined bases with the 3" size being of a bolt down shell/base assembly, is designed for complete leak free operation.



SERFILCO[®]Europe

Broadoak Industrial Park Ashburton Road West, Trafford Park Manchester M17 1RW England

Tel +44 (0) 161 872 1317 Fax +44 (0) 161 873 8027

Email sales@serfilco-europe.com www.serfilco-europe.com